



DELIVERING PREMIUM, DURABLE TRANSPORTATION

Villager

OUR MOST STYLISH AND SOPHISTICATED TRANSPORT VEHICLE YET

We've updated the Villager, one of our most popular vehicles, with enhanced features and best-in-class maneuverability to transport up to eight (8) passengers. The all-new Villager offers industry-leading performance and durability and allows you to streamline your operation with comfortable, reliable transportation. This vehicle is equipped with an updated automotive design and a spacious cabin, which provides a comfortable space for operators and ease of ingress/egress for those on board. Now available with AC drive motor for increased performance, power and acceleration and new premium wheels that enhance the aesthetic appeal of the vehicle.



17 mph











KEY PRODUCT FEATURES

The new Villager includes safety-enhancing features such as LED headlights (with daytime running lamps), a four-wheel braking system, turn signals, tail/brake lights, and a horn to ensure that your quests arrive safely.



LED Headlights with Daytime Running Lamps standard

White



Multiple options available to enhance style and comfort



LED Tail Lights and Turn Signals standard



Easy-to-Clean, Durable, Marine-Grade Vinyl Seats



Standard Colors

Villager 6

Villager 8





GASOLINE

ELECTRIC

ELECTRIC AC

ENGINE/MOTOR	Kohler EFI Gas	48-volt DC	48-volt 3-phase AC
HORSEPOWER	14 hp (10.3 kW) rated @ 3600 RPM per SAE J1940	3.7 hp (2.7kW) rated, Peak 20 hp (14.9 kW)	8 hp (6kW) rated, Peak 16 hp (11.7 kW)
GOVERNOR GUARD	Ground speed	N/A	N/A
BATTERIES	12-volt 500 CCA 105 min reserve	Eight 6-volt flooded lead acid	Eight 6-volt flooded lead acid
CHARGER	N/A	Onboard, automatic, computer-controlled 48-volt DC, 17 amp, UL and CUL listed	Onboard, automatic, computer-controlled 48-volt DC, 17 amp, UL and CUL listed
STEERING	Self-adjusting rack and pinion	Self-adjusting rack and pinion	Se lf- adjusting rack and pinion
FRONT SUSPENSION	Independent leaf spring with dual hydraulic shocks	Independent leaf spring with dual hydraulic shocks	Independent leaf spring with dual hydraulic shocks
BRAKES	4–wheel mechanical drum	4-wheel mechanical drum	4-wheel mechanical drum
PARK BRAKE	Foot operated, multi-lock	Foot operated, multi-lock	Foot operated, mu l ti-lock
BODY AND FINISH	ArmorFlex™ with automotive paint/ clearcoat	ArmorFlex™ with automotive paint/ clearcoat	ArmorFlex™ with automotive paint/ clearcoat
TIRES	18 x 8.50-8, 6-ply rated, premium tread	18 x 8.50-8, 6-ply rated, premium tread	18 x 8.50–8, 6-ply rated, premium tread
BEDLXWXH	N/A	N/A	N/A
WHEELBASE	V6 - 98.5 in (250.2 cm) V8 - 131.5 in (334 cm)	V6 - 98.5 in (250.2 cm) V8 - 131.5 in (334 cm)	V6 - 98.5 in (250.2 cm) V8 - 131.5 in (334 cm)
GROUND CLEARANCE	4.5 in (11.4 cm)	4.5 in (11.4 cm)	4.5 in (11.4 cm)
FUEL TANK CAPACITY	5.5 gal (20.8 L)	N/A	N/A
CURB WEIGHT	V6 - 976 lb (442.7 kg) V8 - 1270 lb (576 kg)	(with batteries) V6 - 1307 lb (592.8 kg) V8 - 1530 lb (693.9 kg)	(with batteries) V6 - 1307 lb (592.8 kg) V8 - 1530 lb (693.9 kg)
CONTROLLER	N/A	500 Amp - Solid State	400 Amp - Solid State
MAX SPEED	17 mph (27 km/h)	16 mph (26 km/h)	15 mph (24 km/h)
LIMITED WARRANTY	3 yr/3000 hr limited powertrain/frame 2 yr limited remaining vehicle	4 yr limited battery 3 yr limited powertrain/frame 2 yr limited remaining vehicle	4 yr limited battery 3 yr limited powertrain/ frame 2 yr limited remaining vehicle