

UNMATCHED VERSATILITY



EXCEPTIONAL RELIABILITY



- Total vehicle capacity of up to 1900 lb (862 kg)
- Delivers the power and ground clearance of a four-wheel drive, but carries even more payload.
- Rustproof, aircraft-grade aluminum frame resists corrosion and withstands impact better than competitors' steel frames.
- Large, four-ply turf tires tread lightly on grass.
- 20 hp-rated (15 kw) Kawasaki industrial-grade gasoline engine and four-wheel hydraulic disc brakes.
- 7.3 in. (19 cm) ground clearance
- Top speed of 19 mph (31 kph)

Club Car

CARRYALL 1500
2WD



1,000 JOBS. ONLY ONE
CARRYALL

CARRYALL 1500 2WD

	GASOLINE
Engine	Kawasaki 4-cycle, industrial grade
Controller	NA
Displacement	675 cc
Cylinders	Twin-cylinder
Valving	OHV
Cooling	Air Cooled
Horsepower (Rated)**	20.1 hp (15.0 kW) rated @ 3400 RPM per SAE J1349
Max Torque**	36.5 ft/lb (49.5 Nm)
Lubrication	Full-pressure, spin-on oil filter
Governor	Automatic ground speed sensing
Transmission	Wide ratio CVT; 3.7:1 low, 0.59:1 high
Front/Rear Differential	Automatic locking rear differential
Gear Selection	Forward/Neutral/Reverse
Gear Ratio	5.39:1 forward, 7.79:1 reverse, 3.3:1 differential
Ignition	Transistorized magneto
Battery	12-volt 500 CCA 105 min Reserve
Passenger Capacity	2
Headlights	2-55w Halogen
Fuel Delivery System	Carburetor
Fuel Capacity	6.5 gal (24.6 L)
Steering Mechanism	Rack and pinion with Tilt Steering
Suspension (Front)	Independent double A-arms with coil-over shocks
Suspension (Rear)	Semi-independent 4-link solid axle
Brakes	Twin piston front, single piston rear hydraulic disk,
Park Brake	Mechanical Disk
Body (Front & Finish)	GE Gelyol high-impact, scratch-resistant, injection molded color, Automotive finish
Body (Frame and Rear)	Tubular aluminum
Tires (Front)	4-ply Turf; 23 x 10.5 x 12
Tires (Rear)	4-ply Turf; 24 x 10.5 x 12
Wheelbase	88.7 in (225 cm)
Overall Height	52.6 in (134 cm)
Overall Length	124.6 in (317 cm)
Bed L x W x H (Cargo Box)	48.8 x 49.8 x 10.9 in (124 x 127 x 28 cm)
Ground Clearance (Differential)	7.3 in (19 cm)
Track Width (Front)	48.8 in. (124 cm)
Track Width (Rear)	48.8 in. (124 cm)
Max Width (w/o Mirrors)	58.5 in. (149 cm)
Outside Clearance Circle (dia.)	316 in (803 cm)
Turning Radius	150.5 in (382 cm)
Intersecting Aisle	N/A
Curb Weight (w/ Batteries)	1410 lb (640 kg)
Vehicle Rated Capacity	Standard 1450 lb (658 kg); With HD Suspension 1900 lb (862 kg)
Bed Load Capacity	Standard 1050 lb (476 kg); With HD Suspension 1500 lb (680 kg)
Trailer Weight Rating	2000 lb (907 kg)
Max Speed	19 mph (31 km/h)
Warranty	2-year/2,000 hour limited



Canopy Top



Solid Windshield



Fold-down Windshield



Heavy-duty Brush Guard



Aluminum Tool Box (Lockable)



Bed Mat




2-inch Front Receiver



2500 lb. Winch



Alloy Wheel



DARK GREY

DARK GREEN

CAMO

Body Colors*

* Non-Standard colors available upon request

** Engine horsepower and torque specifications are provided by the engine manufacturer. Actual horsepower and torque in use may differ and are dependent on environmental conditions as well as maintenance condition of the engine.

