


PEOPLE MOVER

TRANSPORTATION SERIES

ClubCar

	Tempo 2+2		TRANSPORTER		TRANSPORTER" XL		Villager 6		Villager 8	
Club Car						64			R.	
	GASOLINE	ELECTRIC								
ENGINE	Kohler EFI Gas	48-volt DC								
HORSEPOWER	14 hp (10.3 kW) rated @ 3600 RPM per SAE J1940	3.3 hp (2.4 kW) rated; peak 13 hp (9.6 kW)	14 hp (10.3 kW) rated @ 3600 RPM per SAE J1940	3.7 hp (2.7 kW) rated; peak 20 hp (14.9 kW)	14 hp (10.3 kW) rated @ 3600 RPM per SAE J1940	3.7 hp (2.7 kW) rated; peak 20 hp (14.9 kW)	14 hp (10.3 kW) rated @ 3600 RPM per SAE J1940	3.7 hp (2.7 kW) rated; peak 20 hp (14.9 kW)	14 hp (10.3 kW) rated @ 3600 RPM per SAE J1940	3.7 hp (2.7 kW) rated; peak 20 hp (14.9 kW)
GOVERNOR GUARD	Ground speed	N/A								
BATTERIES	12-volt 500 CCA 105 min reserve	Six 8-volt flooded lead acid	12-volt 500 CCA 105 min reserve	Eight 6-volt flooded lead acid	12-volt 500 CCA 105 min reserve	Eight 6-volt flooded lead acid	12-volt 500 CCA 105 min reserve	Eight 6-volt flooded lead acid	12-volt 500 CCA 105 min reserve	Eight 6-volt flooded lead acid
CHARGER	N/A	E.R.I.C. (650 W high frequency)	N/A	DeltaQ QuiQ (1 kW High Frequency)	N/A	DeltaQ QuiQ (1 kW High Frequency)	N/A	Onboard, automatic, computer-controlled 48-volt DC, 17 amp, UL and CUL listed	N/A	Onboard, automatic, computer-controlled 48-volt DC, 17 amp, UL and CUL listed
STEERING	Self-adjusting rack and pinion	Self-adjusting rack and pinion	Self-adjusting rack and pinion	Self-adjusting rack and pinion	Self-adjusting rack and pinion	Self-adjusting rack and pinion	Self-adjusting rack and pinion	Self-adjusting rack and pinion	Self-adjusting rack and pinion	Self-adjusting rack and pinion
FRONT SUSPENSION	Independent leaf spring with dual hydraulic shocks	Independent leaf spring with dual hydraulic shocks	Independent leaf spring with dual hydraulic shocks	Independent leaf spring with dual hydraulic shocks	Independent leaf spring with dual hydraulic shocks	Independent leaf spring with dual hydraulic shocks	Independent leaf spring with dual hydraulic shocks	Independent leaf spring with dual hydraulic shocks	Independent leaf spring with dual hydraulic shocks	Independent leaf spring with dual hydraulic shocks
BRAKES	Rear wheel mechanical drum	Rear wheel mechanical drum	4-wheel mechanical drum	4-wheel mechanical drum						
PARK BRAKE	Foot operated, multi-lock	Foot operated, multi-lock								
BODY AND FINISH	Molded-in color, aluminum finish	Molded-in color, aluminum finish	ArmorFlex™ with automotive paint/ clearcoat, aluminum finish	ArmorFlex™ with automotive paint/ clearcoat, aluminum finish	ArmorFlex™ with automotive paint/ clearcoat, aluminum finish	ArmorFlex™ with automotive paint/ clearcoat, aluminum finish	ArmorFlex™ with automotive paint/ clearcoat, aluminum finish	ArmorFlex™ with automotive paint/ clearcoat, aluminum finish	ArmorFlex™ with automotive paint/ clearcoat, aluminum finish	ArmorFlex™ with automotive paint/ clearcoat, aluminum finish
TIRES	18 x 8.50-8, 4-ply rated, premium tread	18 x 8.50-8, 4-ply rated, premium tread	20 x 10-10, 6-ply rated, premium tread	20 x 10-10, 6-ply rated, premium tread	20 x 10-10, 6-ply rated, premium tread	20 x 10-10, 6-ply rated, premium tread	18 x 8.50-8, 4-ply rated, premium tread	18 x 8.50-8, 4-ply rated, premium tread	18 x 6.50-8, 6-ply rated, premium tread	18 x 6.50-8, 6-ply rated, premium tread
BEDLXWXH	N/A	N/A	37 x 47.5 x 10.5 in (94 x 120 x 27 cm) (Cargo Box)	37 x 47.5 x 10.5 in (94 x 120 x 27 cm) (Cargo Box)	N/A	N/A	N/A	N/A	N/A	N/A
WHEELBASE	65.5 in (166 cm)	65.5 in (166 cm)	99.1 in (252 cm)	99.1 in (252 cm)	132.1 in (336 cm)	132.1 in (336 cm)	98.5 in (250 cm)	98.5 in (250 cm)	131.5 in (334 cm)	131.5 in (334 cm)
GROUND CLEARANCE	4.5 in (11 cm)	4.5 in (11 cm)	5.6 in (14 cm)	5.2 in (14 cm)	5.6 in (14 cm)	5.2 in (14 cm)	4.5 in (11 cm)	4.5 in (11 cm)	4.5 in (11 cm)	4.5 in (11 cm)
FUEL TANK CAPACITY	5.5 gal (20.8 L)	N/A								
CURB WEIGHT	N/A	N/A	932 lb (423 kg) stakeside; 943 lb (428 kg) with rear seat	1494 lb (678 kg) stakeside; 1505 lb (684 kg) with rar seat	1104 lb (501 kg) 8 passenger	1646 lb (747 kg) 8 passenger	773 lb (350 kg)	1105 lb (502 kg)	894 lb (405 kg)	1219 lb (554 kg)
SPEED RANGE	12–15 mph (19.3–24.1 km/h)	5–15 mph (8–24.1 km/h)	15–17 mph (24–27 km/h)	15–17 mph (24–27 km/h)						
LIMITED WARRANTY	3 yr/3000 hr limited powertrain/frame 2 yr limited remaining vehicle	4 yr limited battery 3 yr limited powertrain/frame 2 yr limited remaining vehicle	3 yr/3000 hr limited powertrain/frame 2 yr limited remaining vehicle	4 yr limited battery 3 yr limited powertrain/frame 2 yr limited remaining vehicle	3 yr/3000 hr limited powertrain/frame 2 yr limited remaining vehicle	4 yr limited battery 3 yr limited powertrain/frame 2 yr limited remaining vehicle	3 yr/3000 hr limited powertrain/frame 2 yr limited remaining vehicle	4 yr limited battery 3 yr limited powertrain/frame 2 yr limited remaining vehicle	3 yr/3000 hr limited powertrain/frame 2 yr limited remaining vehicle	4 yr limited battery 3 yr limited powertrain/frame 2 yr limited remaining vehicle
White	Beige	Darl	k Gray	Dark Green	Titanium	Black	Classic Blue		Bright Blue Red Standard Colors (Molded-in)	



1.800.CLUBCAR | 1.706.863.3000 | carryall.com

Villager 6 Villager 8

PREMIUM COMFORT AND DURABILITY

With updated style and sophistication, the all-new Villager allows you to streamline your operation with comfortable, reliable transportation. The Villager moves up to eight (8) passengers and comes with enhanced features and best-in-class maneuverability.







PULL UP IN STYLE

Sleek, compact design gives you a tight turn radius for easy mobility. Plus, transform the backseat into a convenient cargo bed for additional hauling.



TRANSPORTER

FLEXIBLE HAULING

Built for versatility, the Carryall Transporter is designed to carry four to six passengers and additional cargo wherever you need it. Plus, available fit-to-task equipment allows you to customize your vehicle for the job at hand.



TRANSPORTER" XL

PEOPLE, EQUIPMENT & EVERYTHING IN BETWEEN

Our new XL Transporter is the most costeffective and customizable transportation vehicle yet. Go from hauling to transporting or a combination of both—all on the durable Transporter platform.



Built for versatility, the Carryall Transporter is designed to carry four to six passengers and additional cargo wherever you need it.

